

LF4000 EMERGENCY LIGHTING UNIT



CE

FEATURES

- ▶ One-sided type
- ▶ Acrylic transparent reflector with 98% light
- ▶ Flexible wall and ceiling mounting
- ▶ Slim and aesthetic design
- ▶ Long life 18 SMD LED light source
- ▶ Long battery life with smart charging feature

TECHNICAL SPECIFICATIONS

| | |
|-----------------|----------------------------|
| Operation time | 3 hours (without electric) |
| Working Voltage | 230V AC, 50Hz |
| Charge Time | 12 hours |
| Dimensions | 280x180x50mm |
| IP Rating | IP40 |

ORDER DETAILS

- ▶ LF4000 Emergency Lighting Unit

FIELD PRODUCTS

- ▶ The desired pictogram can be pasted and used as a one-sided emergency guidance unit.



PF 6000 EMERGENCY SIGNING UNIT



CE

FEATURES

- ▶ Double-sided type (single-sided if desired)
- ▶ Continuous mode
- ▶ Slim and aesthetic design
- ▶ Wide angle long life 9 SMD LED light source
- ▶ Long battery life with smart charging feature
- ▶ Can apply any kind of pictogram
- ▶ Flexible for wall and ceiling mounting

TECHNICAL SPECIFICATIONS

| | |
|-----------------|----------------------------|
| Operation time | 3 hours (without electric) |
| Working Voltage | 230V AC, 50Hz |
| Charge Time | 12 hours |
| Dimensions | 280x180x50mm |
| IP Rating | IP40 |

ORDER DETAILS

- ▶ PF 6000 Emergency Signing Unit

FIELD PRODUCTS

